

Version: 25 (replaces version 24) Revision: 14.04.2023 Printing date: 14.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: JLM Brake Cleaner 500ml

· Article number: J04100

· UFI: M0CC-R0CR-V002-SEP4

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against -
- · Application of the substance / the mixture Cleaner solvent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

JLM Lubricants b.v.

Schiphol Boulevard 127

1118 BG Schiphol

The Netherlands

Tel: +31 (0) 20 2014995

Further information obtainable from: Research & Development: info@jlmlubricants.com

· 1.4 Emergency telephone number: During normal business hours: Tel: ++31 (0) 20 2014995

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Aerosol 1



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2	H315	Causes skin irritation.
STOT SE 3	Н336	May cause drowsiness or dizziness.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07

GHS09

- · Signal word Danger
- · Hazard-determining components of labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

(Contd. on page 2)



Printing date: 14.04.2023 Version: 25 (replaces version 24) Revision: 14.04.2023

Trade name: JLM Brake Cleaner 500ml

(Contd. of page 1)

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P403 Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Cleansing agent

· Dangerous components:		
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	75-<100%
Reg.nr.: 01-2119475514-35	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 124-38-9	Carbon dioxide	1-<2,5%
EINECS: 204-696-9	Press. Gas (Liq.), H280	

Ingredients according to detergents guidline 648/2004/EC

aliphatic hydrocarbons ≥30%

· Additional information:

Aerosols and containers fitted with a solid atomizer containing substances or mixtures classified as hazardous by aspiration shall not be labelled for that hazard.

The text of the hazard statements mentioned here can be found in chapter 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)



Printing date: 14.04.2023 Version: 25 (replaces version 24) Revision: 14.04.2023

Trade name: JLM Brake Cleaner 500ml

(Contd. of page 2)

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

• 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- \cdot Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurised containers.

 $\cdot \ Further \ information \ about \ storage \ conditions:$

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.



Printing date: 14.04.2023 Version: 25 (replaces version 24) Revision: 14.04.2023

Trade name: JLM Brake Cleaner 500ml

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:		
124-38-9 Carbon dioxide		
AGW (Germany) Long-term value: 9100 mg/m³, 5000 ppm 2(II);DFG, EU		
· DNELs		
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Oral	DNEL Long term-systemic 699 mg/kg bw/day (Consumer)	

773 mg/kg bw/day (Worker)

2035 mg/m3 (Worker)

• Additional information: The lists valid during the making were used as basis.

DNEL Long term-systemic 699 mg/kg bw/day (Consumer)

· 8.2 Exposure controls

Dermal

· Appropriate engineering controls No further data; see section 7.

Inhalative DNEL Long term-systemic 608 mg/m3 (Consumer)

- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

General ventilation

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A2/P2

· Hand protection



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

· Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

(Contd. of page 4)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date: 14.04.2023 Version: 25 (replaces version 24) Revision: 14.04.2023

Trade name: JLM Brake Cleaner 500ml

· Eye/face protection

Safety glasses



Tightly sealed goggles

· Body protection:

Use protective suit. (EN-13034/6)

Full skin covering antistatic, chemical and oil resistant clothing and safety shoes are recommended. (EN1149; EN340&EN ISO 13688; EN13034-6).

• Environmental exposure controls Use a suitable container to prevent environmental contamination.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Aerosol

· Colour: According to product specification

· Odour: Characteristic
· Odour threshold: Not determined.

· Melting point/freezing point: <-20 °C

· Boiling point or initial boiling point and boiling

range 88-106 °C (Hydrocarbons, C6-C7, n-alkanes,

isoalkanes, cyclics, <5% n-hexane)

· Flammability Not applicable.

· Lower and upper explosion limit

• **Lower:** 0,8 Vol % • **Upper:** 7,7 Vol %

• **Flash point:** -9 °C (Hydrocarbons, C6-C7, n-alkanes,

isoalkanes, cyclics, <5% n-hexane)

· Ignition Temperature >200 °C

• **pH** Mixture is non-polar/aprotic.

· Viscosity:

• Kinematic viscosity $\leq 20.5 \text{ mm}2/\text{s}, 40 \text{ °C (L)}$

· Kinematic viscosity

• Dynamic at 20 °C: 0,38 mPas

·Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C: 60 hPa

· Vapor Pressure:

· Density and/or relative density

Density at 20 °C: 0,737 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and

environment, and on safety.

• **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

· Organic solvents: 97,6 % · Solids content: 97,6 %

(Contd. on page 6)



Printing date: 14.04.2023 Version: 25 (replaces version 24) Revision: 14.04.2023

Trade name: JLM Brake Cleaner 500ml

	(Contd. of page 5)
· Change in condition	
· Evaporation rate	Not applicable.
· Information with regard to physical hazard c	elasses
· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container:
	May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flamma	ble
gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
Oral	LD50	>5840 mg/kg (Rat)	
Dermal	LD50	>2920 mg/kg (Rabbit)	
Inhalative	LC50 (4h)	>25 mg/l (Rat)	

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard May be fatal if swallowed and enters airways.

(Contd. on page 7)

(Contd. of page 6)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date: 14.04.2023 Version: 25 (replaces version 24) Revision: 14.04.2023

Trade name: JLM Brake Cleaner 500ml

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:		
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
NOELR (72h)	3 mg/l (Pseudokirchneriella subcapitata)	
EL50 (48h)	3 mg/l (Daphnia magna)	
EL50 (72h)	30-100 mg/l (Pseudokirchneriella subcapitata)	
LL50 (96h)	11,4 mg/l (Oncorhynchus mykiss)	
NOEC (21 days)	0,17 mg/l (Daphnia magna)	
LOEC (21 days)	0,32 mg/l (Daphnia magna)	

- · 12.2 Persistence and degradability Not easily biodegradable
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European	waste catalogue
14 06 03*	other solvents and solvent mixtures
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP14	Ecotoxic

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 8)



Printing date: 14.04.2023 Version: 25 (replaces version 24) Revision: 14.04.2023

Trade name: JLM Brake Cleaner 500ml

(Contd. of page 7)

14.1 UN number or ID number ADR, ADN, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR, ADN	UN1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
IMDG IATA	AEROSOLS, MARINE POLLUTANT AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
· ADN · ADN/R Class:	2 5F
· IMDG	
Class Label	2.1 Gases. 2.1
Class Label	2.1 Gases. 2.1
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Product contains environmentally hazardous substances: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
Marine pollutant: Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user Hazard identification number (Kemler code):	Warning: Gases.
EMS Number: Stowage Code	F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of
Segregation Code	litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of litre: Segregation as for class 9. Stow "separated from" class 9.
	1 except for division 1.4. For AEROSOLS with a capacity above 1 litre:



Printing date: 14.04.2023 Version: 25 (replaces version 24) Revision: 14.04.2023

Trade name: JLM Brake Cleaner 500ml

	(Contd. of page
	Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
· 14.7 Maritime transport in bulk accord	ling to IMO
instruments	Not applicable.
Transport/Additional information:	
· ADR	
· Excepted quantities (EQ)	Code: E0
• •	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P3b FLAMMABLE AEROSOLS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

(Contd. on page 10)



Printing date: 14.04.2023 Version: 25 (replaces version 24) Revision: 14.04.2023

Trade name: JLM Brake Cleaner 500ml

(Contd. of page 9)

- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	75-<100

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · VOC-CH 97,62 %
- · VOC-EU 719,5 g/l
- · Danish MAL Code 3-1
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

Physical and chemical properties: The classification is based on the results of the mixtures tested. Health hazards, Environmental hazards: The method of classification of mixtures based on the constituents of the mixture (sum formula).

· Contact: G. Groot

Date of previous version: 26.09.2022
Version number of previous version: 24

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Aerosol 1: Aerosols – Category 1

Press. Gas (Liq.): Gases under pressure - Liquefied gas

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2